

DU5003

PET Protective Film

Technical Data

• Product Description

It is a PET protective film with polyurethane adhesive single coated.

Key Features


No adhesive residue.

Good performance for die-cutting.

Excellent resistance to demanding environmental conditions.

Have a high degree of temperature resistance.

Construction



Technical Data

Test Item		Unit	Value/Result	Test Method
	PET Film	mm	0.05	-
Thickness	Adhesive	mm	0.01	-
	Total	mm	0.060	-
Peel Force		g/inch	3±2	ASTM D-3330,To Polycarbonate, 180° Peel

 Shelf Life & Storage Conditions Shelf life 12 months from the date of manufacture when stored in original cartons at 18-25 $^{\circ}$ and 30-75% relative humidity.

Notes: The information contained in this data sheet is intended to assist you in designing with Incheng products. The technical information and datas should be considered representative or typical only. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose. The user should determine the suitability of Incheng asdhesive tape for each application.

深圳仁盛化成材料技术有限公司 Incheng Chemical Co., Ltd



Tel: (+86)755-86962203 Fax: (+86)20-38892205 www.incheng.net